

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 930 513 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
21.07.1999 Bulletin 1999/29

(51) Int. Cl.<sup>6</sup>: G01S 5/10, H04Q 7/38

(21) Application number: 98660145.8

(22) Date of filing: 18.12.1998

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

- Rantalainen, Timo  
00200 Helsinki (FI)
- Alanen, Marko  
33200 Tampere (FI)
- Gunnarson, Gudni  
33500 Tampere (FI)
- Hyvärinen, Olli  
33820 Tampere (FI)

(30) Priority: 15.01.1998 FI 980077

(71) Applicant:  
NOKIA MOBILE PHONES LTD.  
02150 Espoo (FI)

(74) Representative:  
Johansson, Folke Anders et al  
Nokia Mobile Phones Ltd.,  
Intellectual Property Rights,  
Kellalahdentie 4  
02150 Espoo (FI)

(72) Inventors:  
• Ruutu, Ville  
02210 Espoo (FI)

## (54) Cellular radio positioning

(57) A cellular radio network based positioning system for determining the position of a mobile station (16). For each base transceiver station (1 to 5) or cell of the network, a fixed list of base transceiver stations is stored by a Mobile Positioning Centre (13). Each list identifies those base transceiver stations which enable the position of a mobile station served by the corresponding base transceiver station (6) to be optimally determined. The list is transmitted to the mobile station (16) via the serving base transceiver station (6) and the mobile station determines an observed time difference for each of the listed base transceiver stations, relative to the serving base transceiver station (6), from signals broadcast by the listed base transceiver stations. The observed time differences are transmitted from the mobile station (6) to the serving base transceiver station (6) and are used by the network to compute the position of the mobile station (16).




Figure 4

EP 0 930 513 A2

## Description

[0001] The present invention relates to a method and apparatus for determining the position of a mobile communications device in a cellular radio telephone network.

[0002] A cellular radio telephone network is made up of Base Transceiver Stations (BTS) each serving a corresponding, geographical "cell" area. Groups of several adjacent cells are organised into what are known as "Location Areas" (LA). If the MS is actively communicating with the network, e.g. the user is conducting a telephone call, the actual cell within the LA in which the MS is present is known to the network. However, when the MS is switched on but not actively used (i.e. it is IDLE or "camping"), the network only knows the LA but not the actual cell in which the MS is present. Cell sizes vary considerably and even if the network knows the cell in which the MS is present the position of the MS can only be identified with a resolution equal to the cell size.

[0003] Future cellular systems may be required to determine the position of a MS with a considerably better precision than can currently be obtained. For example, the United States Federal Communication Commission (FCC) has specified in FCC 94-102 that when a MS is used to make an emergency call the network must be able to locate the MS with an accuracy of 125 meters in 67 percent of cases. Such precise position determination has many other desirable applications such as for taxi dispatch and for monitoring the whereabouts of vehicles, objects and persons etc.

[0004] One possible way to provide the necessary precision is to incorporate a satellite based positioning system, like the Global Positioning System (GPS), into a MS. GPS can be used almost without geographical restrictions, but this solution is complex and increases the cost, size and power consumption of a MS. Moreover, GPS has additional problems including; low signal levels inside buildings, the difficulty in obtaining a clear path to at least three satellites in built-up urban areas, and the relatively long time to obtain a first GPS positional fix after switch-on.

[0005] It appears that a cellular MS locating system based on the cellular radio system offers the best and most practical solution. A number of proposals have been made based either on direction finding, field strength or time measurements. In particular, proposals have been made which rely upon determining the position of a MS from information transmitted to the MS from BTSs serving the cell in which the MS is present and/or adjacent cells.

[0006] One proposal includes triangulation of the position of a MS using at least two direction finding receivers within the network, e.g. incorporated into respective BTSs. Within built-up urban areas, multipath signals will degrade position precision unless the disturbing multipath distortion is removed from observed signals. However, good direction finding receivers having this

capability are expensive and bulky and as such this method is unlikely to be suitable for large-scale cellular radio locating.

[0007] A second proposal relies upon measuring the relative field strengths of signals received at a MS from at least three BTSs. However, it will be appreciated that field strength is likely to vary considerable and in an unpredictable manner over the geographical coverage area of a BTS. This renders the method unsuitable in practise for cellular radio positioning.

[0008] A third proposal requires measurement of time delays in signals transmitted to a MS from several adjacent BTSs (or *vice versa*). Measured delays are converted into respective distances and a simple circle intersecting method can be used to determine a MS position. Such a position determining method, adapted for the GSM cellular radio system, is described for example in WO 92/05672 and WO 97/27711. The methods makes use of transmission Time Advance (TA) values already calculated in GSM transmissions in order to ensure synchronisation of MSs to BTSs (i.e. so that transmissions from a MS arrive at a BTS in the right time slot regardless of the distance between the MS and the BTS). Figure 1 illustrates a TA value based position determining method.

[0009] Figure 2 illustrates another time delay based positioning system in which Observed Time Differences (OTD) are utilised. EP0767594 describes such a system adapted for the GSM cellular radio system. The system has the advantage that OTDs can be obtained without having to register the MS with all of the BTSs used for position determination, as is the case with the TA value based systems.

[0010] Time delay based systems provide a cost-effective and simple solution to the problem of providing high accuracy position determination. However, accuracy is critically dependent upon the position of the BTSs relative to a MS whose position is to be determined. Figure 3a illustrates an example of a good measurement geometry, where each pair of BTSs locates a MS along a hyperbola, and the set of hyperbolas intersect with large contact angles. In contrast, Figure 3b illustrates an example of a bad measurement geometry where the hyperbolas intersect with small contact angles.

[0011] It is an object of the present invention to overcome or at least mitigate the above noted disadvantages. The present invention achieves this and other objects by dynamically notifying a MS of BTSs suitable for position determination purposes, whenever the position of the MS is to be determined, or by notifying the MS of BTSs to be excluded from use in such determinations.

[0012] According to a first aspect of the present invention there is provided a method of determining the position of a mobile communications device within a cellular network, the method comprising the steps of:

transmitting data to the mobile communication device from the cellular network, said data identifying to the mobile communication device a list of radio channels corresponding to respective radio transmitters of the cellular network, said list being determined on the basis of the approximate position of the mobile communication device; and causing the mobile communication device to listen on said identified channels, or on other channels excluding said identified channels, and to determine from information transmitted over the listened to channels data values related to the relative geometry of the mobile communication device and the radio transmitters transmitting the listened to channels; and determining the position of the mobile communication device using said determined data values.

**[0013]** By forcing a mobile communications device to use preselected radio transmitters for position determination measurements, or by excluding certain radio transmitters, the measurement process may be optimised for any given geographical area. The choice of radio transmitters to be used is not left solely to the mobile device and the risk of selecting radio transmitters having a poor measurement geometry, or other disadvantageous properties, is reduced.

**[0014]** Preferably, said transmitters are provided by respective base transceiver stations and the data transmitted to the mobile device identifying the list of radio channels comprises a set of radio channel numbers known to the mobile device.

**[0015]** Preferably, said data values are time relationship values related to the transmission delay times between the mobile device and the radio transmitters transmitting the listened to channels. More preferably, the time relationship values are Observed Time Differences (OTD). Each OTD is the difference between the transmission delay time between the mobile device and one of the radio transmitters transmitting the listened to channels, and the transmission delay time between the mobile device and a radio transmitter of a base transceiver station currently serving the mobile device.

**[0016]** In alternative embodiments of the present invention, the time relationship values are Timing Advance (TA) values equal to twice the transmission delay time between the mobile device and respective ones of the radio transmitters transmitting the listened to channels.

**[0017]** Preferably, said time relationship values are sent by the mobile communications device to the network where said determining step is carried out.

**[0018]** The present invention may also be applied to other position determining methods such as those involving relative field strength measurements and direction finding.

**[0019]** In preferred embodiments of the present invention, the list of radio channels identified to the mobile

device contains those channels which the mobile device should try to listen to in order to obtain said data values from which the position of the mobile device can be determined. In some circumstances, a mobile device may only be able to receive said transmitted information from a sub-set of the listed channels (e.g. because the signal level of the other channels is too low at the mobile device). However, providing that a minimum number of channels can be adequately received (e.g. two) it may still be possible to determine the position of the mobile device.

**[0020]** In other embodiments of the present invention, the network identifies to the mobile device one or more radio channels which should not be used for position determination. This may be desirable, for example, to exclude the use of multiple radio transmitters at the same location. A mobile device may then itself select suitable radio channels, excluding the identified channels, by for example scanning the radio spectrum. The radio channels, or transmitters, selected by the mobile device are identified to the network together with the measurement data.

**[0021]** According to a second aspect of the present invention there is provided apparatus for determining the position of a mobile communications device within a cellular network, the apparatus comprising:

a base transceiver station for transmitting data to the mobile communication device from the cellular network, said data identifying to the mobile communication device a list of radio channels corresponding to respective radio transmitters of the cellular network, said list being determined on the basis of the approximate position of the mobile communication device;

a radio receiver at the mobile communication device for listening on said identified channels, or on other channels excluding said identified channels;

first signal processing means coupled to said radio receiver for determining from information transmitted over the listened to channels data values related to the relative geometry of the mobile communication device and the radio transmitters transmitting the listened to channels; and

second signal processing means for computing the position of the mobile communication device using said determined data values.

**[0022]** According to a third aspect of the present invention there is provided a mobile communications device comprising:

a radio receiver for receiving data transmitted from a serving base transceiver station of a cellular radio network, said data identifying to the mobile communication device a list of radio channels corresponding to respective radio transmitters of the cellular

network, and said list being determined on the basis of the approximate position of the mobile communication device, and said radio receiver being arranged to listen on said identified channels, or on other channels excluding said identified channels;

first signal processing means coupled to said radio receiver for determining from information transmitted over the listened to channels data values related to the relative geometry of the mobile communication device and the radio transmitters transmitting the listened to channels; and

a radio transmitter for transmitting said determined data values to said serving base transceiver station.

**[0023]** For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the accompanying drawings, in which:

Figure 1 illustrates a Timing Advance value method of determining the position of a MS;

Figure 2 illustrates an Observed Time Difference method of obtaining the position of a MS;

Figure 3 illustrates good and bad base transceiver station geometries for use in the Observed Time Difference method of Figure 2; and

Figure 4 illustrates a GSM system arranged to implement a method embodying the present invention.

**[0024]** A typical GSM network that is designed to implement the present invention is shown in Figure 4. The reader is referred to "The GSM System for Mobile Communications" by Mouly and Pautet and "An introduction to GSM" by Redl, Weber and Oliphant", Artech House Publishers Inc, 1995, for an introduction to GSM. The network has *inter alia* Base Transceiver Stations (BTS) 1 to 6, Base Station Controllers (BSC) 7,8 (each BSC controlling a subset of BTSs), a Mobile Switching Centre (MSC) 9 linked to the two BSCs 7,8, and a Short Message Service-Centre (SMS-SC) 10.

**[0025]** The network uses a Home Location Register (HLR) and a Visitor Location Register (VLR), not shown in Figure 4, to maintain the status and LA of a MS, or the address of a foreign network if the MS is not registered to its home network. The MSC 9 of the network communicates with additional networks, including a Public Switched Telephone Network (PSTN), through a Gateway MSC (GMSC) 11, and with an Operation and Maintenance Centre (OMC) 12. The OMC 12 maintains and updates information in the network. A Mobile Positioning Centre (MPC) 13 is added to the conventional GSM network architecture and is used by location applications 14,15 which are also additional to the conventional GSM network architecture.

**[0026]** Figure 4 shows a MS 16 which, for the pur-

poses of this explanation, is assumed to be able to receive transmissions from each of BTSs 1 to 6. At any given time, the MS is registered to only one BTS (BTS 6 in Figure 4) which is termed the "serving" BTS. User data and signaling data are communicated between the network and the MS 16 via this serving BTS 6. However, the MS 16 also continuously monitors the level of signals received from the other surrounding BTSs 1 to 5 for the purpose of facilitating a handover, e.g. when the MS 16 crosses from the serving area of one BTS to that of another BTS. These surrounding BTSs 1 to 5 are identified to the MS 16 by the controlling BSC 8, via the serving BTS 6, when the MS 16 is actively communicating with the network. The MS 16 reports the measured signal levels, over a Slow Associated Control Channel (SACH), to the BSC 8 via the BTS 6. From the received signal levels, the BSC 8 can determine whether the MS 16 should be handed over to another BTS 1 to 5 and/or whether a new "handover" list of BTSs, for monitoring by the MS 16, should be transmitted to the MS 16.

**[0027]** The GSM system is a Time Division Multiple Access (TDMA) based system in which data is transmitted between the network and MSs in time slots allocated to MSs. A TDMA frame is divided into eight time slots. A consequence of this method is the MS 16 must be synchronised with the serving BTS 6 in order to ensure that data transmitted from the MS 16 is received at the BTS 6 in the time slot allocated to the MS 16, and that signals received by the MS 16 are sampled at the correct points in time. Data sent from the BTS 6 to the MS 16 contains synchronisation sequences which are known to the MS 16 and which allow the MS 16 to "lock-on" to the BTS 6 transmissions. The internal clock of the MS 16 is thus synchronised with that of the BTS 6 but with an offset corresponding to the transmission delay time between the serving BTS 6 and the MS 16. The propagation time delay between the MS 16 and the BTS 6 is computed (at regular time intervals) and sent from the BTS 6 to the MS 16 as a Timing Advance Value (TAV) to allow the MS 16 to compensate for the propagation delay in its transmissions.

**[0028]** Assume that one of the network applications 14,15 requests that the position of the MS 16 be determined. This request may be initiated by the MS 16 itself, by the network, or by a remote subscriber or connection, and is passed to the MPC 13. For each BTS, the MPC 13 holds a "locating" list of other BTSs suitable for determining the position of a MS served by that BTS. This information has been provided to the MPC 13 by the OMC 12. Upon receipt of the position determining request, the MPC 13 enquires from the registers (HLR and VLR) in the MSC 9 the status of the MS 16 and, if the MS 16 is active, the serving BTS. If the MS is not currently active, but is reported as switched on, then the MSC 9 will page the BTSs in the LA to determine the serving BTS. The MPC 13 selects the set of BTSs corresponding to the serving BTS and this set or list is transmitted to the MS 16 via the serving BTS 6. The

selected location list may identify a minimum of two BTSs. These may be ones of the BTSs already identified in the handover list, i.e. BTSs 1 to 5, or the location list may include other BTSs. It will be appreciated that BTSs suitable for use in position determination can be relatively remote from the MS 16 as only a unidirectional radio link, from the BTS to the MS 16, is required. The important point is that the identified BTSs have an optimal, or near optimal, geometry for position determination (see Figure 3A).

[0029] The MS 16 has a memory for storing the received location list of BTSs. This memory may be the same memory used to store the handover list of BTSs. The MS 16 listens to each of the radio channels (Broadcast Channels BCCH) of the respective listed BTSs in turn to identify the time of receipt (relative to the MS's internal clock) of known synchronisation sequences. Assuming that synchronisation sequences are transmitted by the serving BTS 6 and one of the listed BTSs at the same time, then the difference in the time of arrival of the sequence at the MS 16 (the Observed Time Difference OTD) would correspond to the difference in the propagation delays between the MS 6 and the two BTSs. This would allow the position of the MS 6 to be placed on a hyperbola as shown in Figure 2. However, it is unlikely that the synchronisation sequences are transmitted by different BTSs at the same time, i.e. there exists a Real Time Difference (RTD) offset between the serving BTS 6 and each listed BTS. The actual propagation delay difference (the Geometric Time Difference GTD) is therefore given by  $GTD = OTD - RTD$ .

[0030] In order to determine the RTD between the serving BTS 6 and one of the listed BTSs, use is made of a radio terminal whose position is fixed and known to the network. Figure 4 illustrates two such terminals 17,18. As the position of the terminal is known, the GTD for any two BTSs is also known. By obtaining an OTD measurement for a pair of BTSs, the RTD value for that pair can be derived. When an OTD measurement is obtained for the MS 6, whose position is unknown and to be determined, the corresponding GTD can be obtained using the measured OTD and the calculated RTD. A list of neighbouring BSTs for which RTDs are required is sent from the serving BTS to the RTD MSs 17,18. For a more detailed description of this computation, the reader is referred to EP0767594.

[0031] As has already been mentioned, Figure 4 shows a system resource 5 termed the Short Message Service-Service Centre SMS-SC. A SMS is a 160 character, text only message format which operates separately from the voice service of the GSM cellular radio network and is specified by the ETSI GSM recommendation GSM 03.40. This recommendation describes the connection of the Service Centre to a Mobile Switching Centre (MSC), such as the MSC 9 in Figure 4, and also describes the operation of the Service Centre (SC) in connection with sending and relaying SMS messages.

This existing service may advantageously be used to relay the MS 16 OTD values to the MPC 13 where the values are used to compute the position of the MS 16.

[0032] The only significant addition to implement the enhanced cellular radio positioning method described above is thus the MPC 13. The MPC can be implemented as a stand alone application (as shown in Figure 4) or may run for example in the SMS Service Centre 10. In either case, the MPC 13 is a database with embedded control, calculation and maintenance programs handling the tasks initiated by the application programs 14,15. The MPC performs the following steps:

- receiving a position determining request from an application 14,15;
- requesting the identity of the BTS serving the MS from the GSM system;
- selecting a list of BTSs based on the serving BTS identity from the database;
- incorporating the selected list in a reporting command;
- requesting the GSM system to send the report command to the MS;
- waiting for a reply while processing other pending position determining requests;
- receiving a reply in the form of a SMS message from the MS via the SMS-SC;
- computing a position using the measurements reported by the MS; and
- sending the computed position to the applications 14,15.

[0033] As an alternative to the use of SMS for sending position data between the serving BTS 6 and the MS 16, data may be transmitted for example on a packet data channel (e.g. in a General Packet Radio Service GPRS) or using an Unstructured Supplementary Data service (USSD).

[0034] In some circumstances, a MS may determine OSDs for BTSs of its own accord, e.g. using the handover list. These may then be sent to the network where the position of the mobile is determined. If the determined position is not accurate enough for the purposes of the network, then a list of BTSs may be sent to the MS from the MPS to enable a new set of OSDs to be determined. This iteration could be carried out several times. It is also possible that a MS could be continuously determining OSDs for the BTSs contained in the handover list, or elsewhere. The current set could then be sent to the network following receipt by the MS of a request for position determination. The iterative process may then be carried out based on the initial approximate determination.

[0035] In the embodiment described above, "raw" OTD values are sent to the MPC 13 where the position of the MS 16 is computed. The MS 16 may of course itself compute its own position if it knows the location of the BTSs identified in the location list and the various

RTDs. This additional information may be sent to the MS together with the location list or separately on a signalling channel.

[0036] In order to improve the accuracy of a position determination measurement, a number of separate measurements may be made using different subsets of BTSs. The MS 16 may receive a first location list, make a first measurement based on this list, then receive a second list, make a second measurement, etc, until an average position measurement of sufficient accuracy is obtained. This averaging method may also be applied to the measurement of RTDs.

[0037] In a modification to the embodiment described above, rather than sending a list of BTSs to the MS 16 which should be used in position determination, the network may send a list of BTSs which should not be used. The BTSs used by the MS 16 may then be selected from, for example, the non-excluded BTS contained in the handover list. This modification may be used advantageously to prevent the use of multiple BTSs present at the same location (it is often the case that several BTSs are mounted on the same mast).

[0038] The present invention may be used to "tag" moving objects, persons, or animals. In such applications, there is no need for voice communication and the MS hardware may be considerably reduced.

[0039] It will be appreciated that whilst the present invention has been illustrated above with reference to the GSM cellular radio telephone standard, the invention is applicable to other cellular telephone standards such as the US CDMA standards and the Japanese PCN standard.

## Claims

1. A method of determining the position of a mobile communications device within a cellular network, the method comprising the steps of:

transmitting data to the mobile communication device from the cellular network, said data identifying to the mobile communication device a list of radio channels corresponding to respective radio transmitters of the cellular network, said list being determined on the basis of the approximate position of the mobile communication device; and  
causing the mobile communication device to listen on said identified channels, or on other channels excluding said identified channels, and to determine from information transmitted over the listened to channels data values related to the relative geometry of the mobile communication device and the radio transmitters transmitting the listened to channels; and  
determining the position of the mobile communication device using said determined data values.

2. A method according to claim 1, wherein said transmitters are provided by respective base transceiver stations and the data transmitted to the mobile device identifying the list of radio channels comprises a set of radio channel numbers known to the mobile device.

3. A method according to claim 1 or 2, wherein said data values are time relationship values related to the transmission delay times between the mobile device and the radio transmitters transmitting the listened to channels.

4. A method according to claim 3, wherein the time relationship values are Observed Time Differences (OTD) each being the difference between the transmission delay time between the mobile device and one of the radio transmitters transmitting the listened to channels, and the transmission delay time between the mobile device and a radio transmitter of a base transceiver station currently serving the mobile device.

5. A method according to claim 3 or 4, wherein said time relationship values are sent by the mobile communications device to the network where said determining step is carried out.

6. A method according to any one of the preceding claims, wherein the list of radio channels identified to the mobile device contains those channels which the mobile device should try to listen to in order to obtain said data values from which the position of the mobile device can be determined.

7. Apparatus for determining the position of a mobile communications device within a cellular network, the apparatus comprising:

a base transceiver station for transmitting data to the mobile communication device from the cellular network, said data identifying to the mobile communication device a list of radio channels corresponding to respective radio transmitters of the cellular network, said list being determined on the basis of the approximate position of the mobile communication device;

a radio receiver at the mobile communication device for listening on said identified channels, or on other channels excluding said identified channels;

first signal processing means coupled to said radio receiver for determining from information transmitted over the listened to channels data values related to the relative geometry of the mobile communication device and the radio transmitters transmitting the listened to chan-

nels; and

second signal processing means for computing the position of the mobile communication device using said determined data values.

5

8. A mobile communications device comprising:

a radio receiver for receiving data transmitted from a serving base transceiver station of a cellular radio network, said data identifying to the mobile communication device a list of radio channels corresponding to respective radio transmitters of the cellular network, and said list being determined on the basis of the approximate position of the mobile communication device, and said radio receiver being arranged to listen on said identified channels, or on other channels excluding said identified channels;

10

15

first signal processing means coupled to said radio receiver for determining from information transmitted over the listened to channels data values related to the relative geometry of the mobile communication device and the radio transmitters transmitting the listened to channels; and

20

25

a radio transmitter for transmitting said determined data values to said serving base transceiver station.

30

35

40

45

50

55




Figure 1




Figure 2






Figure 3

**Figure 4**

**THIS PAGE BLANK (USPTO)**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 930 513 A3**

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
22.11.2000 Bulletin 2000/47

(51) Int. Cl.<sup>7</sup>: **G01S 5/10, H04Q 7/38**

(43) Date of publication A2:  
21.07.1999 Bulletin 1999/29

(21) Application number: **98660145.8**

(22) Date of filing: **18.12.1998**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **15.01.1998 FI 980077**

(71) Applicant:  
**NOKIA MOBILE PHONES LTD.  
02150 Espoo (FI)**

(72) Inventors:  
• **Ruutu, Ville  
02210 Espoo (FI)**

• **Rantalainen, Timo  
00200 Helsinki (FI)**  
• **Alanen, Marko  
33200 Tampere (FI)**  
• **Gunnarson, Gudni  
33500 Tampere (FI)**  
• **Hyvärinen, Olli  
33820 Tampere (FI)**

(74) Representative:  
**Johansson, Folke Anders et al  
Nokia Mobile Phones Ltd.,  
Intellectual Property Rights,  
Keilalahdentie 4  
02150 Espoo (FI)**

### (54) Cellular radio positioning

(57) A cellular radio network based positioning system for determining the position of a mobile station (16). For each base transceiver station (1 to 5) or cell of the network, a fixed list of base transceiver stations is stored by a Mobile Positioning Centre (13). Each list identifies those base transceiver stations which enable the position of a mobile station served by the corresponding base transceiver station (6) to be optimally determined. The list is transmitted to the mobile station (16) via the serving base transceiver station (6) and the mobile station determines an observed time difference for each of the listed base transceiver stations, relative to the serving base transceiver station (6), from signals broadcast by the listed base transceiver stations. The observed time differences are transmitted from the mobile station (6) to the serving base transceiver station (6) and are used by the network to compute the position of the mobile station (16).




Figure 4

EP 0 930 513 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 98 66 0145

| DOCUMENTS CONSIDERED TO BE RELEVANT   |  |   |  |
|---|--|---|--|
| Category  | Citation of document with indication, where appropriate, of relevant passages  | Relevant to claim   | CLASSIFICATION OF THE APPLICATION (Int.Cl.6)         |
| X   | WO 96 35306 A (GANNON STEPHEN MARK ;MUNDAY PETER ROBERT (GB); GOETZ IAN (GB); TEL) 7 November 1996 (1996-11-07)  | 1,3,4, 6-8  | G01S5/10<br>H04Q7/38                                 |
| Y   | * column 9, line 13 - line 30 *<br>* column 11, line 25 - line 30 *  | 5   |  |
| Y,D   | EP 0 767 594 A (NOKIA MOBILE PHONES LTD) 9 April 1997 (1997-04-09)<br>* column 6, line 55 - line 58 *<br>* column 9, line 15 - line 17 *<br>* column 9, line 56 - column 10, line 2 *  | 5   |  |
| A   | SMITH R N ET AL: "AN ADAPTIVE MOBILE WIRELESS HANDOVER", PROCEEDINGS OF THE ANNUAL INTERNATIONAL COMPUTER SOFTWARE AND APPLICATIONS CONFERENCE (COMPSAC),US,LOS ALAMITOS, IEEE COMP. SOC. PRESS, VOL. CONF. 21, PAGE(S) 486-492 XP000740033 ISBN: 0-8186-8106-3<br>* Section 3.2 "Consideration Phase", page 489 - page 490 ; figure 1 * | 1,7,8   |  |
| A   | MOULY M ET AL: "THE PSEUDO-SYNCHRONISATION, A COSTLESS FEATURE TO OBTAIN THE GAINS OF A SYNCHRONISED CELLULAR NETWORK", MRC MOBILE RADIO CONFERENCE,XX,XX, PAGE(S) 51-55 XP000391318<br>* Section: "Knowledge of the "real-time difference" values", page 51 - page 53 *   | 1,7,8   | TECHNICAL FIELDS SEARCHED (Int.Cl.6)<br>H04Q<br>G01S |
| A   | EP 0 662 758 A (ERICSSON GE MOBILE INC) 12 July 1995 (1995-07-12)<br>* abstract; figure 5 *<br>* column 17, line 16 - line 22 *  | 1,7,8   |  |
| The present search report has been drawn up for all claims  |  |   |  |
| Place of search<br>THE HAGUE  |  | Date of completion of the search<br>29 September 2000   | Examiner<br>Niemeijer, R                             |
| CATEGORY OF CITED DOCUMENTS<br>X: particularly relevant if taken alone<br>Y: particularly relevant if combined with another document of the same category<br>A: technological background<br>O: non-written disclosure<br>P: intermediate document |  | T: theory or principle underlying the invention<br>E: earlier patent document, but published on, or after the filing date<br>D: document cited in the application<br>L: document cited for other reasons<br>&: member of the same patent family, corresponding document |  |

EPO FORM 1503 03.92 (P4/C31)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 66 0145

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-09-2000

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|---|---------------------|----------------------------|---------------------|
| WO 9635306 A                              | 07-11-1996          | AU 701275 B                | 21-01-1999          |
|   |                     | AU 5507296 A               | 21-11-1996          |
|   |                     | CA 2219783 A               | 07-11-1996          |
|   |                     | EP 0824840 A               | 25-02-1998          |
|   |                     | JP 11505078 T              | 11-05-1999          |
|   |                     | NO 975041 A                | 30-12-1997          |
|   |                     | NZ 306501 A                | 29-04-1999          |
| EP 0767594 A                              | 09-04-1997          | FI 954705 A                | 04-04-1997          |
|   |                     | US 6108553 A               | 22-08-2000          |
| EP 0662758 A                              | 12-07-1995          | AU 680348 B                | 24-07-1997          |
|   |                     | AU 1725895 A               | 01-08-1995          |
|   |                     | BR 9505638 A               | 09-01-1996          |
|   |                     | CA 2156738 A               | 13-07-1995          |
|   |                     | CN 1124082 A               | 05-06-1996          |
|   |                     | EG 20504 A                 | 30-06-1999          |
|   |                     | FI 954209 A                | 08-09-1995          |
|   |                     | JP 8510610 T               | 05-11-1996          |
|   |                     | SG 55053 A                 | 21-12-1998          |
|   |                     | WO 9519094 A               | 13-07-1995          |
|   |                     | US 5907809 A               | 25-05-1999          |
|   |                     | ZA 9500170 A               | 12-12-1995          |

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**